

INTEGRATED POWER DELIVERY WITH FLEX CIRCUIT
INTERCONNECTION FOR HIGH DENSITY HIGH POWER CIRCUITS FOR
INTEGRATED CIRCUITS AND SYSTEMS

5

ABSTRACT OF THE DISCLOSURE

10 A method and apparatus for electrically interconnecting a first circuit board
having a power conditioning circuit and a second circuit board having a power dissipating
component disposed therebelow along a z (vertical) axis is disclosed. In an illustrative
embodiment, the apparatus comprises a first flexible circuit having a first set of raised
conductive contacts, the first flexible circuit disposed on a first side of the second circuit
board; and a second flexible circuit having a second set of raised conductive contacts, the
second flexible circuit disposed on a second side of the second circuit board opposing the
first side of the second circuit board. A power signal from the power conditioning circuit
is provided to the second circuit board at least in part by one of the first set of raised
15 conductive contacts on the flexible circuit and the second set of raised conductive
contacts on the second flexible circuit and a ground return is provided to the second
circuit board by the other of the first set of raised conductive contacts on the first flexible
circuit and the second set of raised conductive contacts on the second flexible circuit.

CERTIFICATE OF MAILING UNDER 37 CFR 1.10

Express Mail mailing label number: EL815947968US

Date of Deposit: December 4, 2001

I hereby certify that this paper is being deposited with the United
States Postal Service ' Express Mail Post Office To Addressee
service under 37 CFR 1.10 and is addressed to Box Patent
Application, U.S. Patent and Trademark Office, P. O. Box 2327,
Arlington, VA 22202.

By: Isabell Ogata
Name: Isabell Ogata